



Rated Current (AC3/400V):12A~300A

Power Rating (AC3/400V):3kW~335kW

- Compact Size from 5.5~220Hp/ 11~ 300A
- Full Voltage Non-Reversing and Reversing Contactors
- A Wide Range of Common Accessories
- Compatible with RHU bimetal Overload Relay
- Compliance with ROHS
- Approvals: CSA Certified, UL and CE Marked

Catalogue number	IP 40		HUEB-11			HUEB-16			HUB-18			HUB-22			HUB-32R			HUB-40			
	IP 42		HUPB-11			HUPB-16			HUPB-18			HUPB-22			—			—			
	IP 65		HUFB-11			HUFB-16			HUFB-18			HUFB-22			—			—			
Rated Insulation Voltage (Ui) IEC		V		690			690			1000			1000			1000			1000		
Rated Operational Voltage (Ue) IEC		V		690			690			690			690			690			690		
Thermal Current (Ith) IEC/UL		A		25/24			25/32			35/35			40/40			60/55			60/60		
				A	kW	Hp	A	kW	Hp	A	kW	Hp	A	kW	Hp	A	kW	Hp	A	kW	Hp
Rated Power Capacities (Ie) AC3 IEC 60947-4-1	Single	110V		10.5	0.55	0.75	13.5	0.75	1	19.5	1.1	1.5	25.5	1.5	2	35	1.5	2	43	2.2	3
		220V		10.5	1.1	1.5	14	1.5	2	20.5	2.2	3	26	3	4	35	3.7	5	43	5.5	7.5
	Three phase	220V		12	3	4	16	4	5.5	23	5.5	7.5	27	7.5	10	35	9	12	44	11	15
		380V		12	5.5	7.5	16	7.5	10	22	11	15	26	11	15	32	15	20	40	20	27
		415V		11	5.5	7.5	15	7.5	10	21	11	15	21	11	15	32	15	20	40	22	30
		440V		11	5.5	7.5	15	7.5	10	21	11	15	21	11	15	32	15	20	40	22	30
		500V		9	5.5	7.5	13	7.5	10	19	11	15	19	11	15	30	18.5	25	35	22	30
660V		7	5.5	7.5	10	7.5	10	14	11	15	14	11	15	23	18.5	25	26	22	30		
690V		7	5.5	7.5	10	7.5	10	14	11	15	14	11	15	22	18.5	25	26	22	30		
Rated Power Capacities (Ie) AC3 UL 508	Single	110-120V		16	—	1	20	—	1.5	24	—	2	24	—	2	24	—	2	34	—	3
		220-240V		12	—	2	17	—	3	17	—	3	28	—	5	28	—	5	40	—	7.5
	Three phase	200/208V		18	—	5	18	—	5	26	—	7.5	26	—	7.5	25.3	—	7.5	49	—	15
		220-240V		15.2	—	5	15.2	—	5	22	—	7.5	28	—	10	28	—	10	42	—	15
		440-480V		11	—	7.5	14	—	10	21	—	15	27	—	20	27	—	20	40	—	30
550-600V		11	—	10	11	—	10	17	—	15	22	—	20	27	—	25	41	—	40		
For use with bimetallic overload relays		RHU-10/□1			RHU-10/□1			RHU-10/□1			RHU-10/□1			RHU-10/□2			RHU-80/□2				
For use with contactors		CU-11			CU-16			CU-18			CU-22			CU-32R			CU-40				
Contact Configuration		3A1a or 3A1b						3A1a 1b													
Electrical Durability (ops)		1M						1M													
Mechanical Durability (ops)		5M						5M													
 Overall Dimensions (w* h * d) mm / (kg)	IP 40		88*160*107.5 / 0.9						100*170.6*117.3 / 2.0						100*170.6*117.3 / 2.0			130*240*136 / 2.0			
	IP 42		90*184*112 / 0.9						100*194*122.5 / 0.9						—			—			
	IP 65		—						—						—			—			

