



Ratings Range

208/120 V - 60 Hz

Standby	kW	161
	kVA	201,3
Prime	kW	146
	kVA	183



Benefits and features

Rehlko premium quality

- Design offices using the latest technical innovations
- Modern fully certified factories
- A cutting edge laboratory
- The generating set, its components and a wide range of options have been fully developed, prototype tested, factory built, and production tested
- Approved for use with HVO (Hydrotreated Vegetable Oil) according to EN15940

Rehlko premium performances

- Optimized and certified sound levels
- Reliable power, even in extreme conditions
- Optimized fuel consumption
- Compact footprint
- Best quality of electricity, high starting and loading capacity, according to ISO8528-5
- Robust base frames and high-quality enclosures
- Protection of installations and people
- Approved in line with the most stringent standards

Engines

- Rehlko Premium level engines
- High power density, small footprint
- Low temperature starting capability
- Long maintenance interval

Alternator

- Provide industry leading motor starting capability
- Built with a class H insulation and IP23

Cooling

- A compact and complete solution using a mechanically driven radiator fan
- Designed or optimized by Rehlko
- High temperature and altitude product capacity available

Base frame and enclosure

- High quality steel with enhanced corrosion resistance
- Highly durable QUALICOAT-certified epoxy paint
- Minimum 1500 hours of resistance to salt spray in accordance with ISO12944
- Ergonomic access to allow easy maintenance and connection of the generator
- Robust design optimized for transportation

Generator sets ratings

	Hz	Standby rating			Prime rating	
		kWe	kVA	Amps	kWe	kVA
208/120	60	161	201,3	559	146	183
380/220	60	160	200	304	146	182

General Specifications

Manufacturer	Rehlko
Engine ref.	KD83L06T-AW56
Alternator choices	KH01680T
Performance class	G3
Controllers	APM303
Consumption @ 100% load ESP (L/h)*	48
Consumption @ 100% load PRP (L/h)*	41
Emission level	Not certified
Type of Cooling	Radiator
Factory installed enclosures	M149
** Volumetric Fuel consumption is up to 4% higher when using HVO than Diesel Fuel"	

Engine Specifications

Engine brand	Rehiko
Engine ref.	KD83L06T-AW56*
Air inlet system	Turbo
Cylinder configuration	6 - L
Displacement (l)	8,27
Bore (mm) x Stroke (mm)	114 x 135
Compression ratio	16.7:1
Speed (RPM)	1800
Maximum stand-by power at rated RPM 60Hz (kW)	187
Governor type	Electronic
Frequency regulation, steady state (%)	+/- 0.5%

Lubrication System

Oil Filter Quantity and type****	Spin On / 1
Charge Air coolant	Water/Air

****Rehiko recommends the use of genuine oil and filters.

Fuel System

Maximum fuel pump flow 60Hz (l/h)	98
Fuel filter: Qty, type	1 / 1 Primary Engine Filter / Fuel Water Separator
Fuel	Diesel Fuel

* Engine reference may be partially modified depending on genset application, options selected by the customer and lead time required.

Consumption with cooling system

Fuel consumption @ ESP Max Power 60Hz (l/h)	48
Fuel consumption @ PRP Max Power 60Hz (l/h)	41
Fuel consumption @ 75% of PRP Power 60Hz (l/h)	31,8
Fuel consumption @ 50% of PRP Power 60Hz (l/h)	22

Cooling system

Radiator & Engine capacity (l)	29,2
Fan power 60Hz (kW)	10
Fan air flow w/o restriction (m3/s)	5
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene
Radiated heat to ambient (kW)	33
Heat rejection to coolant HT (kW)	115
HT circuit flow rate (l/min)	240
Coolant capacity HT, engine only (l)	12,3
Max coolant temperature, Shutdown (°C)	104
Thermostat begin of opening HT (°C)	82
Thermostat end of opening HT (°C)	95

Exhaust system

Exhaust gas temperature @ ESP 60Hz (°C) 536

Exhaust gas flow @ ESP 60Hz (l/s) 604

Electrical system

Battery voltage (V) 12

Air Intake system

Combustion air flow (l/s) 237

Radiated heat to ambient (kW) 33

Alternator Specifications

Number of pole 4

Technology Brushless

AVR Regulation Yes

Insulation class H

Indication of protection IP23

Number of bearing 1

Number of wires 12

Coupling Direct

Overspeed (rpm) 2250

Voltage regulation at established rating (+/- %) 0,5

Unbalanced load acceptance ratio (%) 8

Alternator standard features

- All models are brushless, rotating-field alternators
- NEMA MG1, IEEE, and ANSI standards compliance for temperature rise and motor starting
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

Note: See Alternator Data Sheets for alternator application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves.



APM303 controller

The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

- Measurements: phase-to-neutral and phase-to-phase voltages, fuel level (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)
- Supervision: Modbus RTU communication on RS485
- Reports: (In option : 2 configurable reports)
- Safety features: Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency (Maximum active power P<66kVA)
- Traceability: Stack of 12 stored events

For further information, please refer to the data sheet for the APM303

Codes and Standards

Engine-generators set is designed and manufactured in facilities certified to standards ISO9001:2015 & ISO14001:2015. The generator sets and its components are prototype-tested, factory built and production tested and are in compliance with the relevant standards:

- Machinery Directive 2006/42/EC of May 17th 2006
- EMC Directive 2014/30/UE
- Safety objectives set out in the Low Voltage Directive 2014/35/UE
- EN ISO 8528-13, EN 60034-1, EN 61000-6-1, EN 61000-6-2, EN 61000-6-3, EN 55011, EN 1679-1 et EN 60204-1

Power ratings definition according to ISO8528-1 (2018-02 edition) and ISO-3046-1

Emergency Standby Power (ESP): The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Average load factor per 24 hours of operation is <70%.

Prime Power (PRP): At varying load, the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour within 12 hour of operation. Average load factor per 24 hours of operation is <70%.

Warranty informations

Standard warranty period:

- for Products in "back-up" service
 - 36 months from the date the Product leaves the plant
 - 24 months from the Product's commissioning date
 - 1,000 running hours

The warranty expires when one of the above conditions is met.

- for Products in "prime" or "continuous" service (continuous supply of electricity, either in the absence of any normal electricity grid or to complement the grid),
 - 24 months from the date the Product leaves the plant
 - 12 months from the Product's commissioning date
 - 2,500 running hours

The warranty expires when one of the above conditions is met.

For more details regarding conditions of application and scope of the warranty please refer to our General "terms & conditions of sales".

Standard scope of supply:

All our open gensets are fitted with:

- Industrial water-cooled DIESEL engine
- Engine electronic governor
- Electric starter & charge alternator
- Battery⁽¹⁾
- Standard air filter
- Electric circuit breaker, adapted to the short-circuit current of the generating set
- Single bearing alternator IP 23 T° rise/ insulation to class H/H
- Welded steel base frame with 85% vibration attenuation mounts
- frame height optimized to allow it to be moved safely by forklift
- enclosure made of new high-quality European steel with enhanced corrosion resistance
- enclosures and base frames tested and analyzed by the French Corrosion Institut
- 100% of tanks tested for permeability
- Personal protection ensured by protective grilles on hot and rotating parts
- Separate 9 dB(A) silencer
- Fuel tank welded inside the genset frame
- Retention bund included for gensets up to 250 kVA ESP
- Emergency stop button on the outside
- Flexible fuel lines & lub oil drain cock
- Oil⁽²⁾ and antifreeze liquid⁽²⁾
- Exhaust outlet with flexible and flanges
- User's manual (1 copy)
- Packing under plastic film

(1) excluded from the supply up to 165 kVA ESP if assembled outside Europe

(2) excluded from the supply up to 830 kVA ESP if assembled outside Europe

Dimensions and Weights

Compact version – Radiator

Overall Size, max., L x W x H, (mm)	2497 x 1103 x 1644
Dry weight (kg)	1740
Tank capacity (L)	344



M149 - Dimensions soundproofed version – Radiator

Overall Size, max., L x W x H, (mm)	3590 x 1147 x 1899
Tank capacity (L)	344
Dry weight (kg)	2300
Acoustic pressure level @1m in dB(A) 60Hz (100% PRP)	84
Acoustic pressure level @7m in dB(A) 60Hz (100% PRP)	74



* dimensions and weight without options

Reference Conditions: 25°C Air Inlet Temperature, 40°C Fuel Inlet Temperature, 100 kPa Barometric Pressure; 10.7 g/kg of dry air Humidity. Intake Restriction set to maximum allowable limit for clean filter; Exhaust Back pressure set to maximum allowable limit; Fuel density at 0.85 kg/L. Data was taken from a single engine test according to the test methods, fuel specification and reference conditions stated above and is subjected to instrumentation and engine-to-engine variability. Test conducted with alternate test methods, instrumentation, fuel or reference conditions can yield different results. Data and specifications subject to change without notice.